



GATOR ROCK BOND BINDER KIT KEEPS STONES IN PLACE

- Create a durable, permeable and decorative surface with the ready to use gator rock binder kit

Mixed GATOR ROCK BOND kit is ready to use with 100% washed and dried riverstone, creating a durable permeable and decorative surface. Great for garden pathways where erosion and drainage is a concern.

IDEAL FOR

- Banding
- Edging and trimming
- Pathways
- Walkways
- Tree wells
- Patios

FEATURES

- Porous and permeable
- Keeps stones in place
- Reduce maintenance and clean-up
- Durable in extreme conditions



LIQUID BINDING AGENT KEEPS STONES IN PLACE

- Create a durable, permeable and decorative surface with your local washed and dried riverstone
- Try the ready to use Gator Rock Bond binder kit.

Mixed GATOR ROCK BOND with 100% washed and dried riverstone, creates a durable permeable and decorative surface. Great for garden pathways where erosion and drainage is a concern.

SUITABLE ROCK TYPES

RIVERSTONE • GRANITE • LIMESTONE • MARBLE

- 3 mm to 10 mm
- Dry and free of dust

GATOR ROCK BOND LIQUID BINDING AGENTS INSTALLATION STEPS

PLEASE NOTE

- Rocks have to be clean, free of dust & 100% dry.
- For pedestrian use only.
- Works above 16°C.
- Allow 24 hours to dry without rain.
- Wear gloves to avoid having binder sticking on your hands.
- Products should be mixed in a masonry mixer or in a wheelbarrow or on a plywood board.
- All tools used could be cleaned using a dissolvent.
- GATOR ROCK BOND has a high gloss appearance when first applied, the shine will gradually diminish within 3 months. This will not affect the bonding of the stones.



A. Always refer to the latest GATOR ROCK BOND LIQUID BINDING AGENT Technical Data Sheet (TDS) at AllianceGator.com before installing GATOR ROCK BOND LIQUID BINDING AGENT.

B. Prepare a solid base by densely compacting 10 cm of crushed stones.



GATOR ROCK BOND KIT Mix one 473 ml container of GATOR ROCK BOND with 100% dry clean riverstone (18.2 kg) provided for 4 minutes.

GATOR ROCK BOND LIQUID BINDING AGENT Mix in a ratio of one container (3.78 L) of GATOR ROCK BOND LIQUID BINDING AGENT with (145 kg) of the below mentioned stones for 4 minutes. Mix products automatically with a masonry mixer or you can manually mix on a sheet of plywood or in a wheelbarrow.



Trowel the mixed riverstone on the surface desired, with a minimal thickness of 13 mm within 20 minutes after mixing.



COVERAGE (KIT)

- 1 kit, at 13 mm surface thickness covers approximately 0.75 to 0.9 sq. m.

COVERAGE (LIQUID BINDING AGENT)

- 3.78 L mixed with 145 kg of dry clean stone covers 7.5 sq. m. at 13 mm thickness



FOR MORE DETAILS, VISIT

AllianceGator.com/europe/