



## GATOR SAND XP G2

### POLYMERIC SAND

FOR PAVER AND NATURAL STONE JOINTS  
UP TO 10 CM IN DRAINAGE APPLICATIONS

#### IDEAL FOR

- Residential & commercial use
- Drainage applications
- Concrete pavers, natural stones, wet cast products, clay pavers and and porcelain tiles with a 3 cm minimum thickness
- Commercial work, steep slopes, pool areas, patios, walkways, driveways and parking areas

#### FEATURES

- No dust, haze free, no blower, one watering
- Drainage applications, **Rain safe 15 minutes** after water activation
- Sets above 0°C
- Faster installation in 4 easy steps
- Can be used on false joint pavers
- Waterproof bag of 20 kg
- 15 year limited warranty

**HAZE FREE ■ NO DUST**  
**NO BLOWER ■ ONE WATERING**  
**RAIN SAFE IN 15 MINUTES**

#### AVAILABLE COLORS



Beige

Slate  
Grey

Ivory

Black



Weed  
sprouting



Damages  
caused by  
insects



Erosion



[AllianceGator.com/europe/](http://AllianceGator.com/europe/)

# 4 SIMPLE STEPS TO INSTALL GATOR SAND XP G2

1



Spread **GATOR XP G2 SAND** with hard-bristle broom. Make sure the **GATOR XP G2 SAND** completely fills the joints. Do not use with other materials in the joints. Leave a layer of **GATOR XP G2 SAND** on the surface to aid in the vibrating and consolidation of **GATOR XP G2 SAND** into joints. For textured or pre-finished surfaces, we recommend removing all the sand from the paver or slab surface prior to using the plate or roller compactor.

2



Vibrate the **GATOR XP G2 SAND** into the paver joints using a vibratory plate compactor. A rubber pad is recommended. A roller compactor or handheld tamper is best for slab or natural stone installations. Joints sand level must be at least 3 mm below top of paver's surface or 3 mm below the chamfer. It is best to compact in several directions to ensure there are no air gaps or voids in the joints. Repeat steps 1 and 2 to ensure joints are filled and consolidated. Narrow joints require more care to completely fill.

3



Sweep off excess **GATOR XP G2 SAND** from the paved surface, first with a hard-bristle broom, then a soft-bristle broom. Take care to leave the height of **GATOR XP G2 SAND** at least 3 mm below top of paver's surface or 3 mm below the chamfer.

4



Shower for a minimum of 30 seconds for 3 sq. m. or until the **GATOR XP G2 SAND** repels the water and the water starts to accumulate over the polymeric sand joints.

## FOR DRAINAGE BASE SYSTEMS (IMPORTANT INSTALLATIONS NOTES)

- A** Always refer to the latest **GATOR XP G2 SAND** Technical Data Sheet (TDS) at AllianceGator.com before installing **GATOR XP G2 SAND**.
- B** Installation of pavers and slabs must be done in accordance with a drainage foundation before adding **GATOR XP G2 SAND**.
- C** Pavers' sides and top surfaces must be completely dry. Do not apply if the paver surface is damp or wet. The damp or wet surface will cause **GATOR XP G2 SAND** to prematurely activate and will lead to the polymers sticking on the paver surface.
- D** Do not apply **GATOR XP G2 SAND**, if the paver joints are damp or wet. This will prevent the **GATOR XP G2 SAND** from properly sliding into the joints and obtaining very densely packed joints, which is critical to the product's performance.
- E** Temperature must be above 0°C with dry conditions and a minimum of 15 minutes of dry weather required after activation of the **GATOR XP G2 SAND**.
- F** For all paver surfaces, and particularly around in-ground pools, there must be a minimum slope of 3 mm per 30 cm away from the edge of the pool or structures to ensure water evacuation off the paver surface.
- G** For the pool coping units, it is mandatory to use mortar in the joints. For the rest of the paver installation around the pool, you can use **GATOR XP G2 SAND**.
- H** Do not sweep **GATOR XP G2 SAND** over asphalt.
- I** Install **GATOR XP G2 SAND** a minimum of 3 mm below top of paver's surface or 3 mm below the chamfer. The filled and cured polymeric sand joints should never be in direct contact with foot traffic or tires, because erosion may occur. \*
- J** For textured or pre-finished surfaces, we recommend removing all the sand from the paver or slab surface prior to using the plate or roller compactor.

\* After a post activation of the **GATOR XP G2 SAND**. The polymeric sand will cycle: In the rainy season the **GATOR XP G2 SAND** will soften and will self-heal, dry and harden again with the sunny season. These cycles could be reproduced over and over without affecting the structural integrity of the **GATOR XP G2 SAND** joints.

**Please Note :** All pavers must be completely interlocked for vehicular and pedestrian use. If pavers are fanned, they are not considered interlocked. **GATOR XP G2 SAND** can be applied when pavers are installed directly open graded aggregates that lock or choke themselves. This means the polymeric sand will not migrate through the voids. Do not apply **GATOR XP G2 SAND** when the pavers are installed directly on aggregates with large voids.

### COVERAGE PER 20 KG GATOR XP G2 BAG 20 CM X 10 CM X 6 CM CONCRETE PAVERS

	BEIGE	SLATE GREY	IVORY	BLACK
3 mm joints	4.2 m <sup>2</sup>	3.9 m <sup>2</sup>	4.2 m <sup>2</sup>	3.6 m <sup>2</sup>
5 mm joints	2.5 m <sup>2</sup>	2.3 m <sup>2</sup>	2.5 m <sup>2</sup>	2.2 m <sup>2</sup>
7 mm joints	1.8 m <sup>2</sup>	1.7 m <sup>2</sup>	1.8 m <sup>2</sup>	1.5 m <sup>2</sup>
10 mm joints	1.3 m <sup>2</sup>	1.2 m <sup>2</sup>	1.3 m <sup>2</sup>	1.1 m <sup>2</sup>

**15 YEAR**  
**LIMITED WARRANTY**  
FOR RESIDENTIAL USE

FOR MORE DETAILS, VISIT

**AllianceGator.com/europe/**