



**GATOR ROCK BOND AND BINDER KIT  
KEEPS STONES IN PLACE**  
TDS Revision Date (dd/mm/yyyy): 22/01/2024



# TECHNICAL DATA SHEET



**Update:** January 22, 2024  
Make sure you have an updated data sheet on hand.

**Description:** Mixed **GATOR ROCK BOND** kit is ready to use with 100% washed and dried riverstone, creating a durable permeable and decorative surface. Great for garden pathways where erosion and drainage is a concern.

**Ideal For:**

- Banding
- Edging and trimming
- Pathways
- Walkways
- Tree wells

**Features:**

- Porous & permeable.
- Keeps stones in place.
- Reduce maintenance & clean up.
- Durable in extreme conditions

**Included In Pail**

- Liquid Binding agent (473 ml)
- Riverstone (18.2 kg)

## APPLICATION INSTRUCTONS:

**PLEASE NOTE :**

- Wear gloves to avoid having binder sticking on your hands. Products should be mixed in a masonry mixer or in a wheelbarrow or on a plywood board.
- For pedestrian use only.
- Works above 16°C.
- Allow 24 hours to dry without rain.
- All tools used could be cleaned using solvent base remover.
- **GATOR ROCK BOND** has a high gloss appearance when first applied, the shine will gradually diminish within 3 months. This will not affect the bonding of the stones.



**Alliance Designer Products Inc.**  
1800 Berlier st., suite 200, Laval, Quebec, Canada H7L 4S4  
Tel.: 450 624-1611 Fax : 450 624-1622  
[www.alliancegator.com](http://www.alliancegator.com) - Email : [info@alliancegator.com](mailto:info@alliancegator.com)



**GATOR ROCK BOND AND BINDER KIT  
KEEPS STONES IN PLACE**

TDS Revision Date (dd/mm/yyyy): 22/01/2024



**APPLICATION INSTRUCTIONS: (CONT.)**



1. A. Always refer to the latest **GATOR ROCK BOND** [Technical Data Sheet \(TDS\)](#) at [AllianceGator.com](http://AllianceGator.com) before installing **GATOR ROCK BOND**.  
B. Prepare a solid base by densely compacting 10 cm of crushed stones.
2. Mix one 473 ml container of **GATOR ROCK BOND** with the dry clean riverstone (18.2 kg) provided for 4 minutes.
3. Trowel the mixed riverstone at a minimal thickness of 13 mm on the desired surface, within 20 minutes after mixing.

**Coverage Per Kit:** 1 kit, at a 13 mm surface thickness, will cover approx. 0.75 to 0.9 sq. m.

**Storage:** Store in a cool, dry, well ventilated area. Store in upright position. Toxic if swallowed. Store at above freezing temperature 0°C. Shelf life is 1 year in original unopened container.

Packaging:	Product	Size	per Pallet
	<b>Gator Rock Bond and Binder Kit</b>	Riverstone 18.2 kg Liquid binding agent 473 ml	48 kits

**WARRANTY:**

**ALLIANCE DESIGNER PRODUCTS INC.** cannot guarantee results as it has no control over surface and sub-surface preparation and product application. **ALLIANCE DESIGNER PRODUCTS INC.** agrees that, if the product is proven to be defective, and on the condition that it was installed pursuant to the method of application of surface and sub-surface preparation described above, then **ALLIANCE DESIGNER PRODUCTS INC.** agrees to refund the purchase price. Proof of purchase is required for any claim. EXCLUSION OF RESPONSIBILITY THE PARTIES AGREE THAT REFUND OF THE PURCHASE PRICE AS STATED IS THE ONLY OBLIGATION OF ALLIANCE DESIGNER PRODUCTS INC. IN ALL EVENTS, **ALLIANCE DESIGNER PRODUCTS INC.,** SHALL NOT BE LIABLE FOR ANY OTHER DAMAGES OR COSTS, DIRECT OR CONSEQUENTIAL. TO THE EXTENT PERMITTED BY LAW, **ALLIANCE DESIGNER PRODUCTS INC.,** EXCLUDES ANY IMPLIED WARRANTY OF QUALITY, MERCHANTABILITY OR FITNESS FOR PURPOSE.



**Alliance Designer Products Inc.**  
1800 Berlier st., suite 200, Laval, Quebec, Canada H7L 4S4  
Tel.: 450 624-1611 Fax : 450 624-1622  
[www.alliancegator.com](http://www.alliancegator.com) - Email : [info@alliancegator.com](mailto:info@alliancegator.com)