



GATOR XTURF CLASSIC BLEND

TDS Revision Date (dd/mm/yyyy): 22/09/2025



TECHNICAL DATA SHEET

Update: September 22, 2025
 Make sure you have an updated data sheet on hand.
 Canada and U.S. dial **1-855-847-7767** or (450) 624-1611

Description: **GATOR XTURF CLASSIC BLEND** artificial turf is the perfect choice for playgrounds and pet areas where aesthetics is important. Designed for residential use, this product features a unique blend of colors, including Gator Forest Green and Gator Lime Green, that will enhance any part of your property. The W-shaped blades of the turf help keep the surface cooler, making it comfortable to use. Additionally, **GATOR XTURF CLASSIC BLEND** is free from heavy metals and harmful substances, and it meets fire resistance standards for both indoor and outdoor applications. This turf is an ideal replacement for natural grass in areas with moderate traffic, requiring low maintenance. Enjoy a beautiful and healthy home life with **GATOR XTURF CLASSIC BLEND**.

Ideal for: Residential and moderate traffic landscaping

- Features:**
- Gator Forest Green or Gator Lime Green
 - Comfortable
 - Soft touch
 - Shorter Pile Height 1.58" (40 mm) ± 3%
 - Face Weight 47 oz/sq.yd ± 5%
 - Total weight of the face and the backing 73 oz/ sq.yd
 - No mowing • No watering
 - 20-year warranty

Packaging:	Product GATOR XTURF CLASSIC BLEND GATOR XTURF CLASSIC BLEND GATOR XTURF CLASSIC BLEND GATOR XTURF CLASSIC BLEND	Size Rolls of 7.5' X 25' (2.29 m x 7.72 m) • 95 lb (43 kg) Rolls of 7.5' X 50' (2.29 m x 15.24 m) • 190 lb (86 kg) Rolls 15' X 33' (4.57 m x 10.0 m) • 253 lb (115 Kg) Rolls of 15' X 100' (4.57 m x 30.48 m) • 760 lb (344 kg)
-------------------	--	--

Typical Properties

SPECS	Description	Units	Gator Forest Green	Gator Lime Green
Color details	Different colors of the yarns used	N/A	Dark Green/Olive	Dark Green/Olive/Lime
Grass Zone Yarn material	Chemical composition	N/A	Polyethylene	Polyethylene
Grass Zone Denier	Density of the turf blade fiber	in grams every 9000 m of fiber yarn. With no. of threads	6 900 / 5	6 900 / 5
Grass Zone D-Tex	Density of the turf blade fiber	in grams every 10 000 m of fiber yarn with no. of threads	7 666 / 5	7 666 / 5



Alliance Designer Products Inc.
 1800 Berlier st., suite 200, Laval, Quebec, Canada H7L 4S4
 Tel.: 450 624-1611 Fax : 450 624-1622 Toll free : 1 866-212-1611
 www.alliancegator.com - Email : info@alliancegator.com



GATOR XTURF CLASSIC BLEND

TDS Revision Date (dd/mm/yyyy): 22/09/2025



SPECS	Description	Units	Gator Forest Green	Gator Lime Green
Thatch zone material	Chemical composition	N/A	Polypropylene	Polypropylene
Thatch Zone Yarn Color	Different colors of the yarns used	N/A	Green/Beige	Green/Beige
Thatch Zone Denier	Density of the thatch fiber	in grams every 9000 m of fiber yarn. With no. of threads	2 800 / 8	2 800 / 8
Thatch D-Ttex	Density of the thatch fiber	in grams every 10 000 m of fiber yarn with no. of threads	3 111 / 8	3 111 / 8
Grass Zone Yarn Shape	Blade shape is so important to the look, function and longevity of your lawn	Omega, C, Diamond, S, M, U, V and W	Wave Blade (keep turf 15 degrees cooler)	Wave Blade (keep turf 15 degrees cooler)
Finished Pile Height	Height of the blades	Inches (mm)	1.58 (40)	1.58 (40)
Finished Face Weight	The number of ounces of fiber per square yard in the face of the turf (not including the backing)	oz/yd ²	47	47
Backing	Type of backing	N/A	Dual PP Layers	Dual PP Layers
Tuft Gauge	Distance between the yarns of synthetic turf	Inches (mm)	3/8 (9,5)	3/8 (9.5)
Total Weight	Weight of the face and the backing	oz/yd ²	73	73
Tuft Bind	Force required to pull a "tuft" out of a carpet	lb	>8	>8
Permeability	Drainage of water	mm /hr	180	180
Fabric Construction	Type of fabric	N/A	Tufted	Tufted
Primary Backing	First coat of backing	N/A	Dual PP Layers	Dual PP Layers
Coating Type	Chemical composition	N/A	Polyurethane	Polyurethane
Primary Backing Weight	Weight of the primary backing only	oz/yd ²	6	6
Secondary Coating Weight	Weight of the secondary backing only	oz/yd ²	20	20
Pile Elongation Break	% of elongation of pile material at break	%	160	160
Flammability	ASTM F-1551-9	N/A	Passed	Passed




Alliance Designer Products Inc.
 1800 Berlier st., suite 200, Laval, Quebec, Canada H7L 4S4
 Tel.: 450 624-1611 Fax : 450 624-1622 Toll free : 1 866-212-1611
 www.alliancegator.com - Email : info@alliancegator.com



GATOR XTURF CLASSIC BLEND


TDS Revision Date (dd/mm/yyyy): 22/09/2025



GATOR XTURF INSTALLATION & APPLICATION


BASE PREPARATION

- A Always refer to the latest **GATOR XTURF** Technical Data Sheet (TDS) available at AllianceGator.com before installing **GATOR XTURF**.
- B Excavate 4-6" (10-15 cm) to prepare for a solid, dense, compacted base foundation of crushed stone. Remove any roots and weeds growing. The levelness and desired shape of your subbase should match your finish grade and allow for proper drainage.
- C You are now ready to lay your geotextile Gator Fabric GF 4.4. Ensure that your Gator Fabric GF 4.4 seam is overlapped by 12 inches (30 cm).
- D The foundation should be built with 4 to 6" (10-15 cm) of compacted 0-3/4" (0-20 mm) crushed stone. Rake and level evenly to achieve your desired grade and slope. Wet your surface before compacting. Run the plate compactor by lift of 2"-3" (5-8 cm) over the entire surface to compact the crushed stone in place. In restricted areas use a hand tamper or a jumping jack. Examine for any high or low spots and adjust before proceeding with the final 3/4" layer of stone dust. The final layer of your foundation that has been compacted, leveled, and sloped should be reflective of the finished yard. (Maximal variant of 3/8" (10 mm) after final compaction) The smoother your base, the smoother your **GATOR XTURF**.
- N.B. To increase drainage, use a 3/4" (20 mm) net stone in drainage channels below your foundation of 0-3/4" (0-20 mm).
- E Now that your foundation is ready for surfacing, it's time to measure and put some reference marks down according to your plan layout and install your first roll of **GATOR XTURF**.



STEP 1 REMOVAL THE OUTER THREE TUFTS


- 1A Determine the **GATOR XTURF** size roll needed to cover the surface and reduce the amount of joint needed for the installation. Roll sizes: (15' x 100' • 15' x 33' • 7.5' x 50' • 7.5' x 25'). Roll out the **GATOR XTURF** on a flat surface. This will help make the next steps quick and easy.
- 1B With the use of a utility knife, remove the outer three tufts on your seaming edge. Trimming the backing tight to the tuft being seamed will ensure straight tufts blades.
- N.B. It is recommended to leave the **GATOR XTURF** exposed to the sun and heat a few hours to ensure dilatation and flatten the **GATOR XTURF**.



FOR STEPS 2 TO 6 • 3 MAIN KEY WORDS TO RETAIN: CUT • GLUE • NAIL

STEP 2 LAYING OF THE FIRST ROLL OF GATOR XTURF

- 2 Keep the edge of the **GATOR XTURF** pulled tight with the help of an artificial turf puller and wave air under it to aid in shifting the pieces into place without disrupting your base. With the first **GATOR XTURF** in place, it's time to bring your next roll. Remove the outer three tufts of your seaming edge, position the second roll of **GATOR XTURF** in the same direction as the initial roll and brush a section of both rolls at the meeting seam to ensure you have the same look of blades, colors and shapes when looking at all angles. Depending on the angle, there could be a variation of texture and color due to lighting.




Alliance Designer Products Inc.
 1800 Berlier st., suite 200, Laval, Quebec, Canada H7L 4S4
 Tel.: 450 624-1611 Fax : 450 624-1622 Toll free : 1 866-212-1611
 www.alliancegator.com - Email : info@alliancegator.com



GATOR XTURF CLASSIC BLEND

TDS Revision Date (dd/mm/yyyy): 22/09/2025





STEP 3 JOINTING THE GATOR XTURFS

3A With the outer three tufts and extended factory backing removed, your **GATOR XTURFS** have a vertical row of blades that line up perfectly with the piece to be seamed. The space between the tufts is 3/8" (9 mm), so you want to ensure the two rows being seam together have that same spacing. Upon lining up your second piece of **GATOR XTURF**, you should observe an open gap of 1/8" to 1/4" (3-6 mm) in width with no excess backing left behind.

3B We are now ready to roll out the **GATOR XTURF SEAM TAPE** centered down your seam with no folds or wrinkles.

Note: To ensure you have no folds or wrinkles, use a Knee Kicker to position the **GATOR XTURF** in place.

3C When the **GATOR XTURF SEAM TAPE** is in place, secure the positioning of the **GATOR XTURF SEAM TAPE** with the help of two 6" (15 cm) **GATOR XTURF NAILS** at both extremities. It's time to spread out some **GATOR XP GLUE**. These nails and seam tape will be covered when the infill is installed.



STEP 4 BINDING THE GATOR XTURF TO THE GATOR XTURF SEAM TAPE


4A Using a glue gun, pour the **GATOR XP GLUE** in a linear or serpentine pattern over the **GATOR XTURF SEAM TAPE** 1" (2.5 cm) away from the middle dotted line of the **GATOR XTURF SEAM TAPE**, both far enough not to spread in the middle of the seam joints. In such an occurrence, clean immediately with solvent such as acetone, thinner or gasoline.

4B With the **GATOR XP GLUE** in place, it's time to put this seam together. Pull both ends back and carefully close the center together evenly (like a zipper). Work slowly and keep your eyes ahead of the closure to assure perfect alignment between the two pieces. You should see a gap of 1/8" to 1/4" (3-6 mm) between them as you lay them down together.

4C With the seam completed, firmly press the ends down and work your way back down the seam applying pressure to help the adhesive penetrate up into the tufts and backing. The seam will all be covered with infill.

Please note:

- 1 It is always safer to double-check your spacing before applying the glue.
- 2 The use of a roller on the seam joints will ensure the transfer of adhesive on the backing.
- 3 To protect the seam joints after gluing, it is also recommended to fix 2 nails at both extremities. These nails and seam will be covered when the infill is installed.
- 4 **GATOR XP GLUE** is a moisture-cure-type adhesive; it is best to apply the **GATOR XP GLUE** and pre-activate it by spraying water before gluing the **GATOR XTURF** to the seam tape. This will speed up the reaction and thereby cure the adhesive. **GATOR XTURF** may be repositioned for up to 30 minutes without losing bond strength. Moisture shortens the open time of polyurethane adhesives. Avoid use when raining or onto standing water. **GATOR XP GLUE** polyurethane adhesive forms a tenacious bond overnight. Cure time varies with temperature and humidity. Make sure the glued seam is set (3-4 hours) before proceeding with the brooming.





GATOR XTURF CLASSIC BLEND

TDS Revision Date (dd/mm/yyyy): 22/09/2025




STEP 5 CUTTING AROUND AN OBJECT OR SEAM

- 5A** When trimming out your project edging for a patio, garden, pavers or other application, with your utility knife in one hand, grab the side of the **GATOR XTURF** being removed and pull it back to expose the backing. The blade of your utility knife should be sharp and just long enough to cut the backing and not the grass blades. When cut, the backing should be tight to any structure edges without touching and a gap no bigger than 1/8" (3 mm).
- 5B** Cutting up to a wall, fence or a boulder requires patience and a sharp blade. Fold the **GATOR XTURF** back, press it tight to the corner and place the blade closest to the object. Lift the **GATOR XTURF** up, cut 6" (15 cm) at a time, lay it back down and check the fit.
- 5C** When cutting around corners, trees or posts, a relief cut will be required. From the furthest outward point, cut through from the backing out to the edge of the **GATOR XTURF**. Remove any excess **GATOR XTURF** so that the next cut is easier to handle.



STEP 6 SECURE GATOR XTURF WITH GATOR XTURF NAILS

- 6.** The 6" (15 cm) non-galvanized spiral **GATOR XTURF NAILS** should sit 1/4" - 1/2" (6-12 mm) away from the edge of the **GATOR XTURF** and be nailed every 4" to 6" (10-15cm) apart. Every 6 feet (1.8 m) from the edge in the roll direction, use a Knee Kicker to remove any loose folds or wrinkles from the **GATOR XTURF**. Secure the turf in place with 6" (15 cm) spiral **GATOR XTURF NAILS** every 12 inches (30 cm) in a straight line. They should be flat against the backing with no turf blades trapped down. (see image 6A-6B).
Note: For putting green, 4" non-galvanized finishing nails will be used.



STEP 7 APPLY GATOR XTURF INFILL SAND (Refer to TDS for quantity of infill sand to use)

- 7A.** **GATOR XTURF** surface requires careful attention. An adjustable drop spreader is ideal for creating a consistent infill layer. However, monitor the rows as the material will settle into the **GATOR XTURF** when applied.
- 7B.** **GATOR XTURF INFILL SAND** requires steady speed and volume for the best results. The more uniformly you spread it, the smoother the final surface will feel underfoot. Apply your infill material in a thin layer each time.
- 7C.** **GATOR XTURF INFILL SAND GATOR BEIGE/GREEN** is the key ingredient for the primary layer, and the beige and green color makes them a natural choice. For pet playgrounds, **GATOR XTURF INFILL SAND GATOR ZEO-WHITE** is widely considered the best topping infill to help reduce and minimize odors. Additionally, **GATOR XTURF INFILL SAND GATOR ZEO-WHITE** is very porous, keeping your **GATOR XTURF** cooler in direct sunlight compared to rubber infill options.




N.B. Ensure the **GATOR XP** glue sets for 3 to 4 hours before brooming.



GATOR XTURF CLASSIC BLEND

TDS Revision Date (dd/mm/yyyy): 22/09/2025



STEP 8: BROOM THE GATOR XTURF

- 8A.** To maintain **GATOR XTURF**, use a stiff bristle broom (8A.1), turf rake, or, Power Broom (8A.2) to reset the blades. Avoid using a metal leaf rake, which can damage the artificial turf blades. Apply firm pressure and walk backward slowly while deepening the infill into the **GATOR XTURF**. Work in rows and overlap your passes for even coverage. Brushing both north-south and east-west is advisable to ensure that no **GATOR XTURF INFILL SAND GATOR BEIGE/ GREEN** is visible and that all the blades stand vertically.
- 8B.** Utilize a leaf blower to remove any **GATOR XTURF INFILL SAND GATOR BEIGE/ GREEN** and/or cut blades remaining on the surface.
- N.B.** After brooming and blowing, lightly mist with water to eliminate static. This also helps the **GATOR XTURF INFILL SAND GATOR BEIGE/GREEN** settle into place and keeps the blades upright.



20-YEAR LIMITED WARRANTY (RESIDENTIAL)

Please note that this limited warranty applies only when the product is used for residential purposes exclusively (homeowners or contractors using the product for single or multi-unit dwellings that are exclusively for residential use). The manufacturer cannot guarantee results as it has no control over surface and sub-surface preparation and product application. (Proper installation of **GATOR XTURF** artificial turf to ensure long-term stability of work, including granular foundation of certified crushed stone of 0-3/4 inch (0-20 mm) (minimum of 4-6 inches (10-15 cm)). However, for a period of 20 years from purchase, the manufacturer agrees that if the product is proven to be defective, and on the condition that it was installed pursuant to the method of application of surface and sub-surface preparation described above, then the manufacturer agrees to refund the purchase price. Proof of purchase is required for any claim.

EXCLUSION OF RESPONSIBILITY

THE PARTIES AGREE THAT REFUND OF THE PURCHASE PRICE AS STATED IS THE ONLY OBLIGATION OF THE MANUFACTURER. IN ALL EVENTS, THE MANUFACTURER SHALL NOT BE LIABLE FOR ANY OTHER DAMAGES OR COSTS WHATSOEVER, (INCLUDING REMOVAL OR REINSTALLATION OF **GATOR XTURF SYSTEM** DIRECT OR CONSEQUENTIAL. TO THE EXTENT PERMITTED BY LAW, THE MANUFACTURER EXCLUDES ANY IMPLIED WARRANTY OF QUALITY, MERCHANTABILITY OR FITNESS FOR PURPOSE. ALLIANCE DESIGNER PRODUCTS INC. excludes any responsibility for use of **GATOR XTURF** for any installation not installed to manufacturer's specifications.

1 YEAR LIMITED WARRANTY (COMMERCIAL)

Please note that when the product is used for other purposes (Mixed-use, commercial, institutional or other), the above terms apply except that the applicable period is reduced to 1 year from purchase. ALLIANCE DESIGNER PRODUCTS INC. excludes any responsibility for use of any **GATOR XTURF SYSTEM** for any installation not installed to manufacturer's specifications.